

Jerith Patriot

6 ga. Horizontal | Dual Rail Design



12' CUSTOM HEIGHT



48" TALL 4 GA.



60" TALL 6 GA.



60" TALL 4 GA.

Jerith Patriot's line of wire fence is a great alternative to both chain link and ornamental aluminum fence. Patriot combines the best features of welded wire mesh with the beauty of ornamental fence to create a unique, affordable, maintenance-free fence.

PRIMARY APPLICATIONS

- Single Family Residences
- Gated Subdivisions
- Golf Courses
- Decorative Accent

JERITH.COM **800-344-2242**

Jerith
ASSA ABLOY

Jerith Patriot

6 ga. Horizontal | Dual Rail Design

4 ga. (.225") or 6 ga. (.192") VERTICAL WIRES | 3-½" for 4 ga. or 1-¾" for 6 ga. VERTICAL SPACING |
6 ga. (.192") HORIZONTAL WIRES | 1" sq. x 18 ga. (.049") RAILS | 2" sq. x 16 ga. (Standard)
or 2-½" sq. x 16 ga. POSTS

STYLE OPTIONS

4 Gauge

6 Gauge

COLORS

- Black



GATES

Gates match the fence style and are available in standard design.



QUALITY & STYLE

When we started manufacturing ornamental aluminum fences around 50 years ago, we made a commitment to producing only durable, high-quality, 100% American-made products. That commitment has become the backbone of our reputation and our promise to you.



LIFETIME LIMITED WARRANTY

Every fence comes with a lifetime warranty, made possible by our FencCoat™ finish and HS-35™ Aluminum Alloy.



DOMESTIC MANUFACTURING

Jerith is committed to providing products that are 100% extruded, coated, fabricated, assembled and packaged in the USA.



TO PLACE YOUR ORDER CALL 800-344-2242 | VISIT JERITH.COM

JERITH PATRIOT | 48", 60" AND 72" HEIGHT OPTIONS

STACK PANELS FOR CUSTOM HEIGHTS

- Ⓐ 4 ga. (.225") or 6 ga. (.192") VERTICAL WIRE
- Ⓑ 3-½" for 4 ga. or 1-¾" for 6 ga. VERTICAL SPACING
- Ⓒ 6 ga. (.192") HORIZONTAL WIRE
- Ⓓ 1" sq. x 18 ga. (.049") RAILS
- Ⓔ 2" sq. x 16 ga. (Standard) 2-1/2" sq. x 16 ga. POST OPTIONS
- Ⓕ 72" STANDARD POST SPACING

Refer to construction specification & tables within this section for recommended post space by bracket type

The logo for Jerith, featuring the word "Jerith" in a stylized, cursive script font.

JERITH PATRIOT | 4 GA. VERTICALS X 6 GA. HORIZONTALS

WIRE MESH | 1" SQ. 18 GA. SQ. TUBE WELDED TO MESH TOP AND BOTTOM | 6' PANEL LENGTH (72" actual width) | 50 SECTIONS PER PALLET

PANEL HEIGHT	ITEM NUMBER	WEIGHT	STOCKING
4'	PA48⊗64SN	24 lbs	<u>B</u>
5'	PA60⊗64SN	27 lbs	<u>B</u>
6'	PA72⊗64SN	32 lbs	<u>B</u>

⊗ = COLOR OPTIONS AVAILABLE | B = Black

⊙ = NON-STOCKED PRODUCT

For details, see Jerith's Sales Policy in the catalog guide.

3-1/2" VERTICAL SPACE

JERITH PATRIOT | 6 GA. VERTICALS X 6 GA. HORIZONTALS

WIRE MESH | 1" SQ. 18 GA. SQ. TUBE WELDED TO MESH TOP AND BOTTOM | 6' PANEL LENGTH (72" actual width) | 50 SECTIONS PER PALLET

PANEL HEIGHT	ITEM NUMBER	WEIGHT	STOCKING
4'	PA48⊗66SN	32 lbs	<u>B</u>
5'	PA60⊗66SN	39 lbs	<u>B</u>
6'	PA72⊗66SN	43 lbs	<u>B</u>

⊗ = COLOR OPTIONS AVAILABLE | B = Black

⊙ = NON-STOCKED PRODUCT

For details, see Jerith's Sales Policy in the catalog guide.

1-3/4" VERTICAL SPACE


ASSA ABLOY

TO PLACE YOUR ORDER CALL 800-344-2242 | VISIT JERITH.COM

Effective: 06/21/22

JERITH PATRIOT | POSTS

AVAILABLE IN BOX QTY ONLY | SCREWS AND FLAT CAPS INCLUDED WITH EACH POST

2" Sq. x 16 Ga. POST

HEIGHT	LENGTH	ITEM NUMBER	BOX QTY	BOX WEIGHT
4'	69"	PA69⊗◇P	?	10 lbs
5'	81"	PA81⊗◇P	?	12 lbs
6'	105"	PA105⊗◇P72	?	15 lbs

2-½" Sq. x 16 Ga. POST

HEIGHT	LENGTH	ITEM NUMBER	BOX QTY	BOX WEIGHT
4'	84"	PA84⊗P25	?	14 lbs
5'	108"	PA108⊗P25	?	18 lbs
6'	132"	PA132⊗P25	?	? lbs

3" Sq. x 12 Ga. POST

HEIGHT	LENGTH	ITEM NUMBER	BOX QTY	BOX WEIGHT
4'	84"	PA84⊗P3	?	? lbs
5'	108"	PA108⊗P3	?	39 lbs
6'	?		?	? lbs

4" Sq. x 11 Ga. POST

HEIGHT	LENGTH	ITEM NUMBER	BOX QTY	BOX WEIGHT
4'	?	?	?	?
5'	?	?	?	?
6'	?	?	?	?

6" Sq. x .1875 Wall POST

HEIGHT	LENGTH	ITEM NUMBER	BOX QTY	BOX WEIGHT
4'	?	?	?	? lbs
5'	108"	PA108⊗P6	?	? lbs
6'	?	?	?	? lbs

⊗ = COLOR OPTIONS AVAILABLE | B = Black


◇ = POST TYPE | L = Line E = End C = Corner

NOTE: Screws and flat caps are included with the posts

Jerith

ASSA ABLOY

JERITH PATRIOT | STEEL SQUARE POSTS



STEEL POSTS

	POST LENGTH	ITEM NUMBER	WEIGHT
2"sq. x 16ga.	6' 9"	WP⊗ 20081	11 lbs
	7' 9"	WP⊗ 20093	13 lbs
	8' 9"	WP⊗ 20105	14 lbs
	10'	WP⊗ 20120	16 lbs
2.5"sq. x 16ga.	11'	WP⊗ 25132	22 lbs
	12'	WP⊗ 25144	24 lbs
2.5"sq. x 12ga.	6'	P⊗ 25072	19 lbs
	7'	P⊗ 25084	22 lbs
	8'	P⊗ 25096	26 lbs
	9'	P⊗ 25108	28 lbs
	10'	P⊗ 25120	31 lbs
	11'	P⊗ 25132	35 lbs
	12'	P⊗ 25144	36 lbs
3"sq. x 12ga.	6'	P⊗ 30072	24 lbs
	7'	P⊗ 30084	30 lbs
	8'	P⊗ 30096	34 lbs
	9'	P⊗ 30108	39 lbs
	10'	P⊗ 30120	43 lbs
	11'	P⊗ 30132	47 lbs
	12'	P⊗ 30144	51 lbs
4"sq. x 11 ga.	6'	P⊗ 40072	39 lbs
	7'	P⊗ 40084	47 lbs
	8'	P⊗ 40096	54 lbs
	9'	P⊗ 40108	61 lbs
	10'	P⊗ 40120	67 lbs
	11'	P⊗ 40132	74 lbs
	12'	P⊗ 40144	81 lbs
6"sq. x .1875" wall	7'	P⊗ 60084	102 lbs
	8'	P⊗ 60096	116 lbs
	9'	P⊗ 60108	131 lbs
	10'	P⊗ 60120	145 lbs
	11'	P⊗ 60132	160 lbs
	12'	P⊗ 60144	174 lbs


⊗ = COLOR OPTIONS AVAILABLE | B = Black

ASSA ABLOY

TO PLACE YOUR ORDER CALL 800-344-2242 | VISIT JERITH.COM

Effective: 06/21/22

JERITH PATRIOT | STEEL PLATED SQUARE POSTS



STEEL POSTS

2.5"sq. x 12ga.


POST LENGTH	PLATE SIZE	ITEM NUMBER	WEIGHT
4'	5" sq. x .25" / .5625" holes (8833G)	Pⓧ25048P	16 lbs
5'	5" sq. x .25" / .5625" holes (8833G)	Pⓧ25060P	19 lbs
6'	5" sq. x .25" / .5625" holes (8833G)	Pⓧ25072P	22 lbs
7'	5" sq. x .25" / .5625" holes (8833G)	Pⓧ25084P	26 lbs
8'	5" sq. x .25" / .5625" holes (8833G)	Pⓧ25096P	28 lbs
9'	5" sq. x .25" / .5625" holes (8833G)	Pⓧ25108P	31 lbs
10'	5" sq. x .25" / .5625" holes (8833G)	Pⓧ25120P	34 lbs
4'	6" sq. x .25" / .5625" holes (5003G)	Pⓧ30048P	20 lbs
5'	6" sq. x .25" / .5625" holes (5003G)	Pⓧ30060P	24 lbs
6'	6" sq. x .25" / .5625" holes (5003G)	Pⓧ30072P	30 lbs
7'	6" sq. x .25" / .5625" holes (5003G)	Pⓧ30084P	34 lbs
8'	6" sq. x .25" / .5625" holes (5003G)	Pⓧ30096P	39 lbs
9'	6" sq. x .25" / .5625" holes (5003G)	Pⓧ30108P	43 lbs
10'	6" sq. x .25" / .5625" holes (5003G)	Pⓧ30120P	47 lbs
4'	8" sq. x .375" / .5625" holes (8876G)	Pⓧ40048P	33 lbs
5'	8" sq. x .375" / .5625" holes (8876G)	Pⓧ40060P	39 lbs
6'	8" sq. x .375" / .5625" holes (8876G)	Pⓧ40072P	47 lbs
7'	8" sq. x .375" / .5625" holes (8876G)	Pⓧ40084P	54 lbs
8'	8" sq. x .375" / .5625" holes (8876G)	Pⓧ40096P	61 lbs
9'	8" sq. x .375" / .5625" holes (8876G)	Pⓧ40108P	67 lbs
10'	8" sq. x .375" / .5625" holes (8876G)	Pⓧ40120P	74 lbs

3"sq. x 12ga.

4"sq. x 11ga.

ⓧ = COLOR OPTIONS AVAILABLE | B = Black

JERITH PATRIOT | POST CAPS



FLAT CAP

Aluminum

SIZE	ITEM NUMBER	QTY	WT. EACH
2"	PAⓧCP2	1	.3 lbs
2-½"	PAⓧCP25	1	.4 lbs
3"	PAⓧCP3	1	.5 lbs
4"	PAⓧCP4	1	.6 lbs
6"	PAⓧCP6	1	.8 lbs

ⓧ = COLOR OPTIONS AVAILABLE | B = Black

ASSA ABLOY

JERITH PATRIOT | PANEL ACCESSORIES

<i>DIAGONAL</i>	SIZE	ITEM NUMBER	QTY	WT. EACH
	87"	PA87DIA	?	? lb
	92"	PA92DIA	?	? lb
	100"	PA100DIA	?	? lb
<i>MALE HINGE</i>	?	PA101	?	? lb
	2.5"	PA10125	?	? lb
<i>POST HINGE TOP</i>	?	PA103	?	? lb
<i>POST HINGE BOTTOM</i>	?	PA105	?	? lb
<i>POST LATCH KEEPER</i>	?	PA108	?	? lb
	2.5"	PA10825	?	? lb
<i>CABLE TIE</i>	?	PACT	?	? lb
	?	PACTP	?	? lb
<i>SELF DRILLING SCREW</i>	#12 x ¾"	⊗1234PSJ	?	? lb
	#12 x ¾"	⊗1234PSJP	?	? lb

⊗ = COLOR OPTIONS AVAILABLE | B = Black

Jerith

ASSA ABLOY

TO PLACE YOUR ORDER CALL 800-344-2242 | VISIT JERITH.COM

Effective: 06/21/22

JERITH PATRIOT | PANEL ACCESSORIES (CONTINUED)

RAIL END FORK	?	PAREF	?	? lb
	?	PAREFP	?	? lb
PLUGS	?	PAPLUGS	?	? lb
POST HDW F/ENDS	?	PAPKEP	?	? lb
POST HDW F/LINES & CORNERS	?	PAPKLPCP	?	? lb

JERITH PATRIOT | POST HARDWARE KITS

ITEM NUMBER	QTY	WT. EACH
PAPKEP	1	1 lb

Includes: 2 Rail Ends, 4 Cable Ties

PAPKLPCP	1	1 lb
----------	---	------

Includes: 4 Rail Ends, 4 Cable Ties

JERITH PATRIOT | CUSTOM FINISHES



TOUCH UP PAINT

.6 OZ.

ITEM NUMBER	QTY	WT. EACH
⊗BOT	1	0.6 oz



SPRAY PAINT

4.5 OZ.

⊗CAN	1	4.5 oz
------	---	--------

⊗ = COLOR OPTIONS AVAILABLE | B = Black

ASSA ABLOY

JERITH PATRIOT | CONSTRUCTION SPECIFICATION 32 31 16

ORNAMENTAL WELDED WIRE FENCES AND GATES

PART 1 - GENERAL

1.01 SECTION INCLUDES

Decorative welded wire fencing, gates, and accessories.

1.02 RELATED SECTIONS

Section ____ - Earthwork

Section ____ - Concrete

1.03 SYSTEM DESCRIPTION

The manufacturer shall supply a total ornamental welded wire fence system of the style, strength, size, and color defined herein. The system shall include all components as required, and shall be fabricated, coated, and assembled in the United States

1.04 QUALITY ASSURANCE

A. The contractor shall provide laborers and supervisors who are familiar with the type of construction involved, and the materials and techniques specified.

B. Manufacturer of fence system must have ten (10) years of documented experience in manufacturing the products specified in this section.

1.05 REFERENCES

- **ASTM A525** — Specification for General Requirements for Steel Sheet, Zinc-coated (Galvanized) by the Hot-Dip Process
- **ASTM A641** — Specification for Zinc-Coated (Galvanized) Carbon Steel Wire
- **ASTM A185** — Specification for Steel Welded Wire Fabric, Plain, for Concrete Reinforcement
- **ASTM B117** — Practice for Operating Salt Spray (Fog) Apparatus
- **ASTM D2247** — Standard Practice for Testing Water Resistance of Coatings in 100% Relative Humidity

1.06 SUBMITTAL

A. Manufacturer's submittal package shall be provided prior to installation.

B. Changes in specification may not be made after the bid date.

C. Samples of assembled materials, components, hardware, accessories, and/or colors, if requested.

1.07 PRODUCT DELIVERY, STORAGE AND HANDLING

A. Upon receipt, materials should be checked for damage that may have occurred in shipping to the job site.

B. Each package shall bear the name of the manufacturer.

C. Store products in manufacturer's unopened packaging.

D. Store materials in a secure and dry area to protect against damage, weather, vandalism, and theft.

E. Transport, handle and store products with care to protect against damage before installation.

PART 2 - PRODUCTS

2.01 MANUFACTURER

A. The fencing system shall be Patriot Ornamental Wire Fence as manufactured by Jerith Manufacturing LLC., 14400 McNulty Road, Philadelphia, PA 19154. Telephone: 800-344-2242; Fax: 215-676-9756; email: sales@jerith.com.

B. Substitutions: [Not permitted / May be submitted in accordance with Section ____].

C. Nominal fence height shall be [48, 60, 72, 96, 120, 144] inches. Fences taller than 72" shall be made by stacking two same height panels on top of each other.

D. Color shall be Black.

2.02 MATERIAL

A. Structural Components: All posts and rails used in the fence system shall be manufactured from coil steel having a minimum yield strength of 55,000 psi. The steel shall be galvanized to meet the requirements of ASTM A525 with a zinc coating weight of 0.60-1.0 ounces per square foot.

B. Infill: Section infill wires shall be steel with a minimum yield strength of 50,000 psi. The steel shall be galvanized to meet the designation of "regular coating" in accordance with requirements of ASTM A641.

2.03 FINISH

A. Pretreatment: A five stage non-chrome pretreatment shall be applied. The final stage shall be a dry-in-place activator which produces a uniform chemical conversion coating for superior adhesion.

ASSA ABLOY

TO PLACE YOUR ORDER CALL 800-344-2242 | VISIT JERITH.COM

Effective: 06/21/22

JERITH PATRIOT | CONSTRUCTION SPECIFICATION 32 31 16

ORNAMENTAL WELDED WIRE FENCES AND GATES

B. Coating: Fence materials shall be coated with a TGIC polyester powder-coat finish system. Epoxy powder coatings, baked enamel or acrylic paint finishes are not acceptable. The finish shall have a cured film thickness of at least 2.0 mils.

C. Tests: The cured finish shall meet the following requirements:

1. Humidity resistance of 1,000 hours using ASTM D2247.
2. Salt-spray resistance of 1,000 hours using ASTM B117.
3. Outdoor weathering shall show no adhesion loss, checking or crazing, with only slight fade and chalk when exposed for 3 years in Florida facing south at a 45 degree angle.

2.04 FABRICATION

A. Fence Sections shall be manufactured with 1" square x 18 gauge (.049") tubing welded every 12" to the top and bottom of welded wire panels. Welded wire panels shall be comprised of [4 (.225"), 6 (.192")] gauge (Washburn & Moen Standard) vertical wires and 6 (.192") gauge horizontal wires. 4 gauge vertical wires shall be placed 3½" on center. 6 gauge vertical wires shall be placed 1¾" on center. Horizontal wires shall be 6 gauge and spaced to provide style differences but no further apart than would allow substantial rigidity of vertical wires. Horizontal and vertical wires shall be assembled by automatic machines or other suitable mechanical means that will ensure accurate spacing and alignment of all members of the finished fabric. The wires shall be connected at every intersection by electric resistance welding in accordance with all requirements in ASTM A185. Sections shall be capable of supporting a 550 lb. load applied vertically at midspan and a concentrated load of 225 lbs. applied horizontally at midspan without permanent deformation.

B. Posts shall be [2", 2½", 3", 4"] square x [16 (.065"), 14 (.080"), 12 (.105"), 11 (.125")] gauge steel tubing. Posts shall be spaced 70" apart from inside face to inside face. Steel rail ends shall be screwed to terminal posts to receive the 1" square top and bottom rails. The rails shall be secured to the rail ends by stainless steel screws. Steel caps shall be provided with all posts.

C. Residential and light commercial grade gates shall be assembled using gate uprights with 1" outside cross-section dimensions having 7/8" tubes welded to them. A Fence Section shall then be cut to size and secured to two uprights using stainless steel screws. A 1" x .125" diagonal brace shall be provided, cut to length, cold galvanized, touched up, and screwed into position from the top hinge side to the bottom latch side of the gate. All gates shall support a 300 lb. vertical load on the latch side of the gate without collapsing.

D. Heavy duty grade gate frames shall consist of 2" square x .125" wall gate uprights and 1.5" x 1.5" x .125" U-channels for top and bottom members welded at each connection with a 1" x .125" wall diagonal brace welded into place. Infill of matching Fence Section shall be welded into frame.

2.05 WARRANTY

The entire fence system shall have a written 8 Year Warranty against rust and defects in workmanship and materials. In addition, the finish shall be warranted not to crack, chip, peel, or blister for the same period.

PART 3 – EXECUTION:

3.01 PREPARATION

- A. Verify** areas to receive fencing are completed to final grades and elevations.
- B. Ensure** property lines and legal boundaries are clearly established.
- C. Remove** any surface irregularities which may cause interference with the installation of the fence.

3.02 FENCE INSTALLATION

- A. Install** fence in accordance with the manufacturer's instructions.
- B. Excavate** post holes to proper depth to suit local conditions for stability and support of the fence system without disturbing the underlying materials. Excavate deeper as required for adequate support in soft and loose soils.
- C. Set** fence posts in concrete footers at 70" spacing from inside of post to inside of post. Note that this fence must be stepped for installations on a slope. It can not follow the grade.
- D. Center** and align posts in holes to required depth. Place concrete around posts and tamp for consolidation. After tamping, check alignment of posts, and make necessary corrections before the concrete hardens.
- E. Insert** rail ends into horizontal rails and fasten in place to the posts.

Jerith

ASSA ABLOY

JERITH PATRIOT | CONSTRUCTION SPECIFICATION 32 31 16

ORNAMENTAL WELDED WIRE FENCES AND GATES

3.03 GATE INSTALLATION

- A. Set gate posts plumb and level for gate openings specified in construction drawings.
- B. Install gates to allow full opening without interference after concrete has hardened around gate posts. Adjust hardware for smooth operation. Install one drop rod for double gates.

3.04 ACCESSORIES

Install post caps and other accessories to complete fence.

3.05 CLEANING

- A. Contractor shall clean site of debris and excess materials. Post hole excavations shall be scattered uniformly away from posts.
- B. If necessary, clean fence system with mild household detergent and clean water. Excess concrete must be removed from posts and other fencing material before it hardens.



JERITH PATRIOT | LIMITED LIFETIME WARRANTY

ORNAMENTAL WELDED WIRE FENCES AND GATES

As a leading manufacturer of quality fence products, Jerith Manufacturing Co., Inc. warrants that the FencCoat™ finish on its Patriot Ornamental Wire Fences will not peel, crack, chip, or blister for a period of 8 years from the initial purchase date. Jerith also warrants that its wire fences will be free from defects in workmanship and materials for the same period.

This warranty does not extend to damage caused by improper application, installation, or use; abuse; accident; alteration; negligence; or acts of God. There are no other express warranties except as stated herein. This warranty is issued to the original purchaser and is not transferable. This warranty must be registered within 30 days of installation with Jerith.

If the product should fail to conform with this warranty, Jerith shall repair or replace the defective parts at its discretion. The purchaser shall provide Jerith with written notice of the failure, along with proof of purchase, and the nature of the defect. Jerith reserves the right to inspect the material at its plant to determine the validity of a claim. If it is valid, all removal and re-installation costs of the materials are the responsibility of the purchaser.


The above constitutes the complete warranty by Jerith and no other agreement, written or implied, is valid. No person is authorized to change or modify this warranty. Recovery for consequential or incidental damages are hereby excluded. This warranty gives you certain specific legal rights, and you may also have other rights which vary from state to state.

The logo for Jerith, featuring the word "Jerith" in a stylized, cursive script font.

JERITH PATRIOT | SINGLE SWING GATE SPECIFICATIONS

2"sq x 12ga GATE ENDS | 2"sq x 12ga RAILS | 2" x 6" x 6ga WELDED WIRE | 3.5' - 16' NOMINAL OPENINGS

SINGLE SWING
DIMENSIONAL DRAWING




HGBS-25 / HGBS-3
180 HINGE & STRONG
ARM LATCH KITS

SINGLE SWING
HARDWARE KITS & POST
INTERSPACES

OPENING	LEAF WIDTH*	HC	LC	P _S
3.5'	42"	1.25"	3"	46.25"
4'	48"	1.25"	3"	52.25"
5'	60"	1.25"	3"	64.25"
6'	72"	1.25"	3"	76.25"
7'	84"	1.25"	3"	88.25"
8'	96"	1.25"	3"	100.25"
9'	108"	1.25"	3"	112.25"
10'	120"	1.25"	3"	124.25"
11'	132"	1.25"	3"	136.25"
12'	144"	1.25"	3"	148.25"
13'	156"	1.25"	3"	160.25"
14'	168"	1.25"	3"	172.25"
15'	180"	1.25"	3"	184.25"
16'	192"	1.25"	3"	196.25"

W = width* | HC = hinge clearance | LC = latch clear-
ance | P_S = gate post spacing**

* From outside to outside | ** From inside to inside




Jerith

JERITH PATRIOT | DOUBLE SWING GATE SPECIFICATIONS

2"sq x 12ga GATE ENDS | 2"sq x 12ga RAILS | 2" x 6" x 6ga WELDED WIRE | 7' - 32' NOMINAL OPENINGS

DOUBLE SWING
DIMENSIONAL DRAWING



HGBD
180 HINGE & STRONG
ARM LATCH KIT


DOUBLE SWING
HARDWARE KITS & POST
INTERSPACES

OPENING	LEAF WIDTH*	HC	LC	P _d
7'	42"	1.25"	3"	89.5"
8'	48"	1.25"	3"	101.5"
10'	60"	1.25"	3"	125.5"
12'	72"	1.25"	3"	149.5"
14'	84"	1.25"	3"	173.5"
16'	96"	1.25"	3"	197.5"
18'	108"	1.25"	3"	221.5"
20'	120"	1.25"	3"	245.5"
22'	132"	1.25"	3"	269.5"
24'	144"	1.25"	3"	293.5"
26'	156"	1.25"	3"	317.5"
28'	168"	1.25"	3"	341.5"
30'	180"	1.25"	3"	365.5"
32'	192"	1.25"	3"	389.5"

W = width (x2)* | HC = hinge clearance (x2) | LC = latch clearance

P_d = gate post spacing**

* From outside to outside | ** From inside to inside



Jerith

JERITH PATRIOT | V-FOLD WELDED WIRE GATES

GATE HARDWARE SOLD SEPARATELY

HEIGHT	OPENING	ITEM NUMBER	WEIGHT	STOCKING
4'	3½'	5WP⊗ 04-42	55	⊗
	4'	5WP⊗ 04-48	60	⊗
	5'	5WP⊗ 04-60	70	⊗
	6'	5WP⊗ 04-72	79	⊗
	7'	5WP⊗ 04-84	100	⊗
	8'	5WP⊗ 04-96	109	⊗
	9'	5WP⊗ 04-108	118	⊗
	10'	5WP⊗ 04-120	128	⊗
	11'	5WP⊗ 04-132	137	⊗
	12'	5WP⊗ 04-144	147	⊗
	13'	5WP⊗ 04-156	156	⊗
	14'	5WP⊗ 04-168	165	⊗
	15'	5WP⊗ 04-180	175	⊗
	16'	5WP⊗ 04-192	184	⊗
5'	3½'	5WP⊗ 05-42	64	⊗
	4'	5WP⊗ 05-48	70	⊗
	5'	5WP⊗ 05-60	80	⊗
	6'	5WP⊗ 05-72	90	⊗
	7'	5WP⊗ 05-84	115	⊗
	8'	5WP⊗ 05-96	125	⊗
	9'	5WP⊗ 05-108	135	⊗
	10'	5WP⊗ 05-120	146	⊗
	11'	5WP⊗ 05-132	156	⊗
	12'	5WP⊗ 05-144	166	⊗
	13'	5WP⊗ 05-156	177	⊗
	14'	5WP⊗ 05-168	187	⊗
	15'	5WP⊗ 05-180	197	⊗
	16'	5WP⊗ 05-192	208	⊗

⊗ = COLOR OPTIONS AVAILABLE | B = Black

⊙ = NON-STOCKED PRODUCT

For details, see Ameristar's Sales Policy in the catalog guide.

NOTE: Double Drive Gates consist of two gate leafs

Jerith

ASSA ABLOY

TO PLACE YOUR ORDER CALL 800-344-2242 | VISIT JERITH.COM

Effective: 06/21/22

JERITH PATRIOT | V-FOLD WELDED WIRE GATES

GATE HARDWARE SOLD SEPARATELY

HEIGHT	OPENING	ITEM NUMBER	WEIGHT	STOCKING
6'	3½'	5WP⊗06-42	73	⊗
	4'	5WP⊗06-48	79	⊗
	5'	5WP⊗06-60	90	⊗
	6'	5WP⊗06-72	102	⊗
	7'	5WP⊗06-84	130	⊗
	8'	5WP⊗06-96	141	⊗
	9'	5WP⊗06-108	152	⊗
	10'	5WP⊗06-120	164	⊗
	11'	5WP⊗06-132	175	⊗
	12'	5WP⊗06-144	186	⊗
	13'	5WP⊗06-156	197	⊗
	14'	5WP⊗06-168	209	⊗
	15'	5WP⊗06-180	220	⊗
	16'	5WP⊗06-192	231	⊗

⊗ = COLOR OPTIONS AVAILABLE | B = Black

⊗ = NON-STOCKED PRODUCT

For details, see Ameristar's Sales Policy in the catalog guide.

NOTE: Double Drive Gates consist of two gate leafs

ASSA ABLOY

JERITH PATRIOT

JERITH PATRIOT | 6 GA. HORIZONTAL | DUAL RAIL DESIGN

Jerith

ASSA ABLOY

TO PLACE YOUR ORDER CALL 800-344-2242 | VISIT [JERITH.COM](https://www.jerith.com)

Effective: 06/21/22

Jerith

JERITH PATRIOT

JERITH PATRIOT | 6 GA. HORIZONTAL | DUAL RAIL DESIGN

Jerith

ASSA ABLOY

TO PLACE YOUR ORDER CALL 800-344-2242 | VISIT [JERITH.COM](https://www.jerith.com)

Effective: 06/21/22